

Technical characteristics of modifications Tral 5.0, Tral 5.0 PoE , Tral 5.1, Tral 5.1 PoE:

	Tral 5.0	Tral 5.0 PoE	Tral 5.1	Tral 5.1 PoE
Analog Inputs	1 video, 1 audio			
Max frame rate (main channel)	25 fps			
Video quality (main channel)	704×576 (interpolated)		704×576 (deinterlacing)	
Video resolution and frame rate (additional channel)	320x240, 5 fps		-	
Video compression	H.264 or MPEG4			
Switching colour/ black and white	automatic			
Network protocols	TCP, UDP, IP, RTP, SMTP, NTP, DHCP, NFS, SMB, E-mail client			
Digital interfaces	Fast Ethernet 10/100 Base-T, USB 2.0			
External sensor interface	Opto-isolator, «dry contact»			
Supply voltage	9...16 V DC	48 V PoE	9...16 V DC	48 V PoE
Power consumption	2 W	2.3 W	2 W	2.3 W
Dimensions	120×55×26 mm	120×55×30 mm	120×55×26 mm	120×55×30 mm
Weight	87g	103g	87g	103g
Operational temperature	0°C ... +55°C (+32°F ... +131°F)			
In the mode of no-break power	-20°C ... +55°C			
In the mode of no-break power in a hermetic box	-40°C ... +55°C			